

G4-D02A 1.6W



G4-D02A	
Product Size	10*38mm
Power	1.6W
LED Quantity	1PCS
Net weight	2.5g
LED type	COB 1505
Luminous Efficiency	>105 LM/W
Beam angle	300°
Input Voltage	DC 12V 50-60Hz
Power Factor	>0.99
Rendering Index	>80
IP Grade	IP65
CCT(K)	3000K,4000K,6000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years



G4-D03 2.3W



G4-D03	
Product Size	13.5*38.5mm
Power	2.3W
LED Quantity	1PC
Net weight	2.6 g
LED type	COB 1508
Luminous Efficiency	>105 LM/W
Beam angle	300°
Input Voltage	DC 12V 50-60Hz
Power Factor	>0.99
Rendering Index	>80
IP Grade	IP65
CCT(K)	3000K,6000K
Certification	/
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years



G9-D02 2.5W



G9-D02	
Product Size	17*52mm
Power	2.5W
LED Quantity	1PC
Net weight	8.5g
LED type	COB 1508
Luminous Efficiency	>105LM/W
Beam angle	300°
Input Voltage	AC 120V 50-60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years



G9-CR45LEDA 3.5W



G9-CR45LEDA 4.5W



G9-CR64LED 6W



E12-CR45LEDA 3.5W



G9-CR45LEDA	
Product Size	17.5 *55mm
Power	3.5W
LED Quantity	45PCS
Net weight	14.5g
LED type	SMD 2835
Luminous Efficiency	> 110 LM/W
Beam angle	360°
Input Voltage	AC 120V 50-60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K,4000K,5000K,6000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years

G9-CR45LEDA	
Product Size	17.5*55mm
Power	4.5W
LED Quantity	45PCS
Net weight	14.5g
LED type	SMD 2835
Luminous Efficiency	> 110 LM/W
Beam angle	360°
Input Voltage	AC 120V 50-60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K,4000K,5000K,6000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years

G9-CR64LED	
Product Size	18*58mm
Power	6W
LED Quantity	64PCS
Net weight	18g
LED type	SMD 2835
Luminous Efficiency	> 110 LM/W
Beam angle	360°
Input Voltage	AC 120V 50-60Hz
Power Factor	>0.74
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K,4000K,5000K,6000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years

E12-CR45LEDA	
Product Size	17.5 *54mm
Power	3.5W
LED Quantity	45PCS
Net weight	15.2g
LED type	SMD 2835
Luminous Efficiency	> 110 LM/W
Beam angle	360°
Input Voltage	AC 120V 50-60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K,4000K,5000K,6000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25,000H
Quality Warranty	2years

