



4" Slim Round Panel LED

Options:

- Single CCT
- 3Way CCT adjustable
- 120-347V
- 5Way CCT adjustable



Specification				
	Single CCT	3Way CCT adjustable	5Way CCT adjustable	120-347V
Model No.	VO-RP4W10-120-40-D VO-RP4W10-120-50-D WH VO-RP4W10-120-60-D	VO-RP4W10-120-D-3WY BN	VO-RP4W10-120-D-5WY WH/BK	VO-RP4W10-347-D-3WY WH
Size	4.9"x0.8" (Lamp) 3.3"x3.3"x1.2" (Driver)			
Beam Angle	140°			
Input	120V 60Hz			
Power Factor	>0.9			
Dimmable	Yes			
Power (W)	10W			
Luminous Flux	750LM			
Color Temperature	3000K/4000K/5000K/6000k	3000K/4000K/5000K adjustable	2700K/3000K/3500K/4000K/ 5000K adjustable	3000K/4000K/5000K adjustable
CRI	>80			
SDCM	<7			
Life Tume (Hrs)	50000			
Certification Requirements	ETL / ES / 5 Years			

Features

- Safe - This downlight is IC Rated and airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation.

It is ETL certified, which means it has met the nationally recognized safety requirements.

- Energy Efficient - With Energy Star labeled, it consumes only 10 watts, equivalent to 60W halogen. That's so easy to save up to 90% on the electric bill.

- Long Lifespan - The lifespan is as long as 50,000 hours. we provide 5 years warranty and lifetime technical support.

