

## Mini Dual Head Emergency Light



### Features:

- . Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- . Innovative, easy installation in minutes.
- . Suitable for wall mount applications.
- . Universal J-box mounting pattern.
- . 120/347VAC Dual Voltage operation.
- . 2 x 1W ultra bright LED lamp heads for emergency mode.
- . Luminous Flux: more than 200 LM.
- . Built-in 3.6V 900mAh Nickle cadmium battery for minimum 90 minutes emergency operation.
- . Maximum 24 hours for full recharge time.
- . Test switch and charge indicator.
- . UL and CULus listed.
- . 32°F (0°C) to 104°F (40°C) indoor damp location listed.
- . Five years warranty for the electrical parts and housing.
- . Three years warranty for battery
- . CSA listed meets all requirement in C22.2 No.141-10, Suitable for Canada market.

### Specification

Model No.	BY-Z3125E
Charging Time	24h
AC Voltage	120V/347V 50-60Hz
AC Charging Current (MAX)	100mA
DC Charging Voltage	4.2V
DC Charging Current (MAX)	75mA
Distance Time	≥90mins
Discharge Current	700mA-900mA
Luminous Flux	≥200LM
Color Temperature	6000K-7000K

### Dimensions:

