www.votatec.ca

Slim Flush Mount LED










Specifications:

	WHITE	BLACK
Model	HM08-PR16-30W120-3CCT-WSA/WH	HM08-PR16-30W120-3CCT-BSA/BK
Power	30W	30W
ССТ	3000K / 4000K / 5000K	3000K / 4000K / 5000K
Brightness	2400LM	2400LM
LED Type	SMD2845 / 224PCS	SMD2845 / 224PCS
Voltage	120V	120V
Power Efficiency	≥0.9	≥0.9
RA	≥80	≥80
Beam Angle	110°	110°
Dimension	15.6″x0.9"	15.6″x0.9"

Features:

- Built-in driver, 24mm thickness
- White & Black two different colors available
- Good Quality LGP & diffuser Plate
- Stable design for the whole structure
- SMT technology, ensuring accurate for LEDs on FPCB
- 3 CCT tunable
- 120V, Triac dimming
- 5 Years warranty













16" Slim Flush Mount LED

3 Way CCT Adjustable

www.votatec.ca

Perfect LED Mounting

Uniform Light Distribution


Black dots and shadow on the light, un-uniform lighting, which are the headache in the LED panel field.

The LED Light Strip

SMT technology, ensuring accurate positions for LEDs on FPCB Good quality LGP and diffuser plate Stable design for the whole structure Above ensures u iform lighting, no black dots and shadow.



Surface Mounted With J-Box




3CCT


Changeable 3000K/4000K/5000K



Dimensions:



HM08-PR16-30W120-3CCT-WSA



HM08-PR16-30W120-3CCT-WSA