

## Slim Integrated T5 LED(Linkable)



**3W**



**5W**



**9W**



**13W**



**18W**

## Specifications

MODEL	VO-T5FIXW3FT0.5 -120-3WAY-S-D	VO-T5FIXW5FT1 -120-3WAY-S-D	VO-T5FIXW9FT2 -120-3WAY-S-D	VO-T5FIXW13FT3 -120-3WAY-S-D	VO-T5FIXW18FT4 -120-3WAY-S-D
Lumen Output	250LM	500LM	900LM	1300LM	1800LM
Power	3W	5W	9W	13W	18W
Length(Inch)	0.5ft	1ft	2ft	3ft	4ft
Lumen Efficiency	100lm/w				
CCT	3000K/4000K/5000K				
CRI	>80Ra				
Input Voltage	120V/ 60Hz				
Power Factor	0.9				
Beam angle	135°				
Operating Temperature	-20~+45 C				
Dimmable	Yes				
CERTIFICATION	cUL				
Life time (Hrs)	50000hrs				

### Safety


Comply with UL Requirement, safety in use.RoHS compliance. Ecodesign. Replacement incandescent:

### Features

working voltage :108~132V  
No flicker, uniform light. Compatible to traditional lamps.

### Application

Operating Temperature: -20~+45°C  
Indoor Basic Lighting and Directional Lighting.  
Replace incandescent/halogen/CFL lamps.



## Compatible Dimmer List

Dimmer Brand	Model#
Lutron	DVCL-153PLH
Leviton	6681
Lutron	S600-P
Lutron	DV600-P15
Leviton	6674
MACL	153M
Lutron	PD-6WCL

## Dimensions

Length x width x height			
	Length	Width	Height
0.5ft	6 inches	1 inches	0.6 inches
1ft	12 inches		
2ft	23.7 inches		
3ft	35.6 inches		
4ft	47.5 inches		

## Integrated T5 LED (Linkable)




Power Cord  
(Sell Separately for 1ft & 2ft)



connecting cable  
(Sell Separately)



3.93ft power cord with plug on one end and another male end  
(Sell Separately)



wire box with female end & on/off switch  
(Sell Separately)

## HARDWARE CONTENTS ( Included in package )

⊕ x2 Mounting Screws (4x22mm)

x2 Clips

⊕ x2 Mounting Screws (4x16mm)

x2 Roll plug

female end cap

3 3/4" Knock outs

Link with Male End of T5 Fixture/ connecting cable ( sold separately )

