



Features:

- Isolated Driver
- Flicker Free
- 15.7" (40cm) Cable

| Specification | | |
|----------------------------|--|--|
| | Single CCT | 5Way CCT adjustable |
| Model No. | VO-RP4W9-120-30-D VO-RP4W9-120-40-D VO-RP4W9-120-50-D VO-RP4W9-120-60-D WH | VO-RP4W9-120-D-5WAY/ WH VO-RP4W9-120-D-5WAY/ BK |
| Size | 4.92"x0.8" (Lamp) 3.98"X2.8"X1.38" (Driver) | |
| Beam Angle | 120° | |
| Input | 120V 60Hz | |
| Power Factor | >0.9 | |
| Dimmable | Yes | |
| Power (W) | 9 W | |
| Luminous Flux | 750LM | |
| Color Temperature | 3000K/4000K/5000K/6000k | 2700K/3000K/3500K/4000K/5000K adjustable |
| CRI | >80 | |
| SDCM | <7 | |
| Life Tume (Hrs) | 50000 | |
| Certification Requirements | ETL / ES / 5 Years | |

Features

- Safe - This downlight is IC Rated and airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation.

It is ETL certified, which means it has met the nationality recognized safety requirements.

- Energy Efficient - With Energy Star labeled, it consumes only 9 watts, equivalent to 60W halogen. That's so easy to save up to %90 on the electric bill.

- Long Lifespan - The lifespan is as long as 50,000 hours. we provide 5 years warranty and lifetime technical support.

