




The canless LED recessed downlights in 3" round, square, comes with airtight back seal cap, prevent dust from falling into the lamp body. It is with IC rated & airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation. offer a high end but cost-effective and enemy saving recessed lighting solution in both residential and commercial applications. It is with remote junction box with isolated dimming driver inside eliminating the use of traditional recessed housing can, total a 3 in 1 design with light, trim and junction box, which help on easy installation and labor cost saving.

### Technical Specifications

Model No.:	Round: VO-GRP3W8-120-D-5WAY/WH VO-GRP3W8-120-D-5WAY/BK Square: VO-GSP3W8-120-D-5WAY/WH VO-GSP3W8-120-D-5WAY/BK
Nominal Wattage(W)	8W
Lumens Delivered(LM)	640Lm
Equivalency	40 W INC
Efficiency(LM/W)	80
Cut Out Size	Φ72MM (2-7/8")
Beam Angle	°40
CRI	>90
Color Temperature(K)	2700K/3000K/3500K/4000K/5000K ADJ
L70 Lifetime(Hrs)	>50,000
Voltage	120 Volts, Triac EVL Dimming %100-%10
Power Factor	>0.9
IC Rated	Yes
Air Tight	Yes
Material	Cold Forged Heat Sink/ Die-cast Trim Ring
Exterior Finish	Matte White/Black
Mounting	Recessed With Remote Junction Box, No Housing Required
Operating Temperature	-4°F to 104°F
Certificates	cETLus
Environment	Indoor Wet Location
Warranty	5 Years Limited



### Dimensions

