

Project : _____
 Type : _____
 Drawn by : _____
 Catalogue No. : _____
 Date : _____



Specifications




Model No.		□ VO-RR4W9-120-D-5WAY/WH
General	Watts	9W/7.5W/6W
	Lumen	800/640/510LM
	CCT	2700K/3000K/3500K/4000K/5000K
	HID Equivalent	75W
	Volts	120V
	CRI	>80
	Beam Angle	38°
	Hours Rated	50000 hours
	Min Compartment Size	Ø5"x2.4"
Electrical	Operating Frequency	50-60Hz
	Power Factor	>0.9
	Operating Position	Recessed In Ceiling
	Surge Protection	Built-in surge protection-2.5KV
	Operating Temperature	-20°C /-4°F to 40°C/104°F
Physical	Lens Material	PC
	Housing Color	White
	Weight (Kg)	0.58
Additional Information	Additional Info	5 way Power
	Rated For Enclosed Fixture	Yes
	Warranty	5 years
Compliance	Safety Listing	CETLus-Listed
	Location Rating	Damp
	Energy Star	YES
	DLC Approved	No

Features & Specifications

Construction	<ul style="list-style-type: none"> • Construction: Aluminum Trim With PC LENS • Multiple LED array for uniform illumination • CCT switches and power switch are placed discretely outside the driver housing
Mounting	<ul style="list-style-type: none"> • R4 recessed downlight trims are engineered for retrofit installation, compatible with standard 4-inch recessed can housings in the North American market.
Performance Data	<ul style="list-style-type: none"> • Available in 2700k/3000k/3500k/4000k/5000k selectable color temperature • 80+ CRI • Electrical ratings: 120v • Estimated life of over 50000 hours to L70 • ELV&TRIAC Dimming • 2.5kV surge protection (standard) • Operating temperature: -20°C /-4°F to 40°C/104°F
Compliances	<ul style="list-style-type: none"> • cETL certified for damp • IP20 • ES listed

Dimensions & Weights

Model	VO-RR4W9-120-D-5WAY/WH
Diameter in.(mm)	5" (127.5)
Height in. (mm)	0.24" (60.8)
Net weight (Kgs)	0.58



Product Details

- The color of the light is more uniform softer



- CCT Adjustable:
2700K/3000K/3500K/
4000K/5000K



- Power Adjustable:
9W/7.5W/6W

Compatible Dimmers

BRAND	MODEL
HILUTRON	DVCL-153PLH
LUTRON	S600-P
LUTRON	DV600-P15
LUTRON	MACL-153M
LUTRON	CTCL-153P
LUTRON	MS-OPS2
LUTRON	CTCL-153P
LUTRON	PD-6WCL
LEVITON	6674
LEVITON	6681

Dimming range : 10%-100%


This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance.

Read and comply to the dimmer installation instructions. Some dimmers may require more than one product for stable operation.

recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

Lumen Details

Model No.:	Watts (W)	2700K		3000K		3500K		4000K		5000K	
		Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)
VO-RR4W9-120-D-5WAY/WH	9W	831LM	95	895LM	103	936LM	107	967LM	111	941LM	107
	7W	827LM	98	780LM	106	818LM	110	842LM	114	837LM	111
	6W	602LM	101	640LM	109	668LM	113	684LM	117	690LM	115



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Votatec customer service representative to confirm inventory levels at time of order

