

www.votatec.ca

4" Slim Round Panel LED





4" Slim Round Panel LED **Options:**

- FT4 Wire






















UL 263 «Fire Test of Buidling Construction & **Materials**»

*Designed to Provide 120 minutes of Fire Resistance

*Tested by CSAfire

Specification	
	5Way CCT adjustable
Model No.	VO-RP4W10-120-D-5WY WH
Size	4.9"x0.8" (Lamp) 100*68.3*34.4MM(Driver)
Beam Angle	140°
Input	120V 60Hz
Power Factor	>0.9
Dimmable	Yes
Power (W)	10W
Luminous Flux	750LM
Color Temperature	2700K/3000K/3500K/4000K/5000K adjustable
CRI	>80
SDCM	<7
Life Tume (Hrs)	50000
Certification Requirements	ETL / ES /5 Years



www.votatec.ca

Features

- Safe - This downlight is IC Rated and airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation.

It is ETL certified, which means it has met the nationality recognized safety requirements.

- Energy Efficient With Energy Star labled, it consumes only 10 watts, equivalent to 60W halogen. That's so easy to save up to %90 on the electric bill.
- Long Lifespan The lifespan is as long as 50/000 hours, we provide 5 years warranty and lifetime technical support.

