

Project : _____

Type : _____

Drawn by : _____

Catalogue No. : _____

Date : _____



VO-FG25W9-26



VO-FG25W9-26-30-D-M

Specifications

Model No.		☐ VO-FG25W9-26	☐ VO-FG25W9-26-30-D-M
General	CCT	☐ 3000K ☐ 4000K	3000K
	Watts	9W	9W
	Lumen	1000Lm	1000Lm
	Base	E26	E26
	Volts	120V	120V
	CRI	>80	>80
	Beam Angle	360°	360°
	Hours Rated	15,000Hrs	15,000Hrs
Electrical	Product Size	4.57"(H) x3.15"(Φ)	4.57"(H) x3.15"(Φ)
	IP Grade	IP20	IP20
	Power Factor	>0.7	>0.7
	Storage temperature	-25°C ~ 40°C	-25°C ~ 40°C
Physical	Operating Temperature	-25°C ~ 40°C	-25°C ~ 40°C
	Lens Material	Glass	Glass
	Bulb Head Color	Clear	Milky
	Weight (g)	45 (±5g)	45 (±5g)
Additional Information	Additional Info	Dimmable	Dimmable
	Rated For Enclosed Fixture	No	No
	Warranty	2 Years	2 Years
Compliance	Certification	cUL	cUL

Features & Specifications

Performance Data


- Available color temperature in 3000K/4000K
- 80+ CRI
- Electrical ratings : AC 120V 50-60Hz
- Estimated life: 15,000 hours
- Dimming Capable
- 2.5kV surge protection (standard)
- -20°C~+40°C (the best in 25°C)

Compliances


- cUL
- IP20

Dimensions & Weights

Model	VO-FG25W9-26	VO-FG25W9-26-30-D-M
Diameter in. (mm)	3.15(80)	3.15(80)
Height in. (mm)	4.57(116)	4.57(116)
Net weight (g)	45 (±5g)	45 (±5g)




VO-FG25W9-26



VO-FT25W5.5-120-30-D-M

Product Details



Lumen Details

Model No.:	Watts (W)	2700K		3000K		4000K		5000K		6000K	
		Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)
VO-FG25W9-26	9W	—	—	1121	148	1071	139	—	—	—	—
VO-FG25W9-26-30-D-M	9W	—	—	1088	131	—	—	—	—	—	—



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Votatec customer service representative to confirm inventory levels at time of order

