


Project : _____
 Type : _____
 Drawn by : _____
 Catalogue No. : _____
 Date : _____



VO-FST12W5.5-12-50-D



Specifications

Model No.		<input type="checkbox"/> VO-FST12W5.5-12-50-D
General	Watts	5.5W
	Lumen	600Lm
	Base	E12(Anti-shock)
	CCT	5000K
	Volts	120V
	CRI	>80
	Beam Angle	360°
	Hours Rated	15,000Hrs
	Product Size	3.96"(H) x1.57"(Φ)
Electrical	IP Grade	IP20
	Power Factor	>0.7
	Storage Temperature	-25°C ~ 40°C
	Operating Temperature	-25°C ~ 40°C
Physical	Lens Material	Glass
	Bulb Head Color	Clear
	Weight (g)	20 (±2g)
Additional Information	Additional Info	Dimmable
	Rated For Enclosed Fixture	No
	Warranty	3Years
Compliance	Certification	cUL

Features & Specifications

Performance Data


- Available color temperature in 5000K
- 80+ CRI
- Electrical ratings : AC 120V 50-60Hz
- Estimated life: 15,000 hours
- Dimming Capable
- 2.5kV surge protection (standard)
- -20°C~+40°C (the best in 25°C)

Compliances


- cUL
- IP20

Dimensions & Weights

Model	VO-FST12W5.5-12-50-D
Diameter in. (mm)	1.57(40)
Height in. (mm)	3.96(100.5)
Net weight (g)	20 (±2g)



Product Details



Lumen Details

Model No.:	Watts (W)	2700K		3000K		4000K		5000K		6000K	
		Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)
VO-FST12W5.5-12-50-D	5.5W	—	—	—	—	—	—	649	130	—	—



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Votatec customer service representative to confirm inventory levels at time of order

