

Project : _____

Type : _____

Drawn by : _____

Catalogue No. : _____

Date : _____



VO-FT25W5.5-120



VO-FT25W5.5-120-30-D-M

Specifications



Model No.		VO-FT25W5.5-120			VO-FT25W5.5-120-30-D-M
General	CCT	☐ 3000K	☐ 4000K	☐ 5000K	3000K
	Watts	5.5W			5.5W
	Lumen	600Lm			600Lm
	Base	E12(Anti Shock)			E12(Anti Shock)
	Volts	120V			120V
	CRI	>80			>80
	Beam Angle	360°			360°
	Hours Rated	15,000Hrs			15,000Hrs
	Product Size	3.43"(H) x0.98"(Φ)			3.43"(H) x0.98"(Φ)
Electrical	IP Grade	IP20			IP20
	Power Factor	>0.7			>0.7
	Storage temperature	-25°C ~ 40°C			-25°C ~ 40°C
	Operating Temperature	-25°C ~ 40°C			-25°C ~ 40°C
Physical	Lens Material	Glass			Glass
	Bulb Head Color	Clear			Milky
	Weight (g)	14 (±2g)			14 (±2g)
Additional Information	Additional Info	Dimmable			Dimmable
	Warranty	3Years			3Years
Compliance	Certification	cETLus			cUL

Features & Specifications


Performance Data	• Available color temperature in 3000K/4000K/5000K • 80+ CRI • Electrical ratings : AC 120V 50-60Hz • Estimated life: 15,000 hours • Dimming Capable • 0.5kV surge protection (standard) • -20°C~+40°C (the best in 25°C)
Compliances	• cUL & cETLus • IP20

Dimensions & Weights

Model No.	VO-FT25W5.5-120	VO-FT25W5.5-120-30-D-M
Diameter in. (mm)	0.98(25)	0.98(25)
Height in. (mm)	3.43(87)	3.43(87)
Net weight (g)	14 (±2g)	14 (±2g)




Product Details



Lumen Details

Model No.:	Watts (W)	2700K		3000K		4000K		5000K		6000K	
		Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)	Lumen Output (LM)	Efficiency (LM/W)
VO-FT25W5.5-120	5.5W	—	—	637	130	630	125	662	133	—	—
VO-FT25W5.5-120-30-D-M	5.5W	—	—	590	113	—	—	—	—	—	—



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Votatec customer service representative to confirm inventory levels at time of order

