

Project : _____
 Type : _____
 Drawn by : _____
 Catalogue No. : _____
 Date : _____



15A
YGB-094WR

20A
YGB-095WR



Specifications

Model No.	□ YGB-094WR	□ YGB-095WR	
General	Rated Voltage	125V,60Hz	125V,60Hz
	Rated Power	1800W~2400W	1800W~2400W
	Button times	>3000 times	>3000 times
	Mechanical life	6000 times	6000 times
	Dielectric voltage withstand	1500V(AC)	1500V(AC)
	Trip threshold	5mA	5mA
	Trip time	< 25mS	< 25mS
	Short-circuit current	10KA	10KA
	Wires	14-12AWG	14-12AWG
	Power Supply	Neutral & Live Wire & Grounding	Neutral & Live Wire & Grounding
	Installation Method	In-wall	In-wall
	Application	Indoor	Indoor
	Physical	MOL	4.13in
MOW		1.68in	1.68in
MOH		1.60in	1.60in
Material		Plastic+Metal	Plastic+Metal
Housing Color		White	White
Weight (Kg)		0.12	0.12
Operating Environment	Operating Temperature	-35°C (-31F) TO 66°C (150.8F)	-35°C (-31F) TO 66°C(150.8F)
Additional Information	Stand	UL943 / UL948 / CSA C22.2 No.144.1	UL943 / UL948 / CSA C22.2 No.144.1
	Warranty	2 years	2 years
	Safety Listing	cUL	cUL
Compliance	Energy Star	No	No
	DLC Approved	No	No

Features & Specifications

Construction

- Adopting high-quality thermoplastic materials with reasonable structural design, ensuring excellent strength and durability

Features

- Protective door (TR): It can prevent children from using foreign objects to come into contact with the live parts of the socket, and keep children away from the risk of electric shock
- Weather Resistant: enhanced corrosion resistant components to withstand more moist or humid location
- Provide continuous ground fault protection, which can detect actual ground faults and trip even during self check
- The indicator light (LED) provides clear feedback on power and protection status
 Green light: GFCI is powered, properly reset, and functioning normally
 Red light: Fault condition or failed internal self-test
 Flashing red (on supported models): End-of-life warning; device must be replaced
- Ground Fault Circuit Interrupter
- Safe-Test
- Compatible with most switch panels

Compliances

- cUL certified

Dimensions & Weights

Model	YGB-094WR/YGB-095WR
Length in.(cm)	4.13 (10.5)
Width in. (cm)	1.68 (4.28)
Height in. (cm)	1.60 (4.07)
Net weight (lbs)	0.12



